Lc 2/40

PROTECTING AGENT



DESCRIPTION

The Lc 2/40 Protection Agent is used to prevent unintentional contamination during the work process.

APPLICATION

Lc 2/40 Protection Agent is applied to the surfaces to be protected by means of the LcM nozzle and thus prevents the escaping adhesive residue, markings or friction or contamination from sticking to the workpiece. In addition, Lc 2/40 Protection Agent prevents the peeling away of the protective film on the edgebanding.

AREA OF APPLICATION

EDGE FINISHING MACHINE

- Wetting pressure roll
- Wetting corner area (cross-gluing)
- Wetting edgebanding surface
- Wetting tools
- Wetting draw blade

PHYSICAL & CHEMICAL DATA

PHYSICAL STATE	Liquid
COLOUR	Blue
ODOUR	Solvent
INITIAL BOILING POINT	78 °C
FLASH POINT	12 °C
DENSITY	0,81 g/cm³
VOC CONTENT	91 % (737,1 g/l)

SAFETY, TRANSPORT & STORAGE

TRANSPORT	UN 1170, class 3, packing group II
HS CODE	38140090
CLASSIFICATION	**Danger** H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.
COMPOSITION	Mixture of ethanol
STORAGE	Keep the container tightly closed. Store in a cool and dry place. Protect against sunlight
SHELF LIFE	in unopened container for 2 years.

AVAILABLE PACK SIZES

5L | 10L | 30L | 200L | 1000L

DISPOSAL

1. Disposal of PE packaging AVV 15 01 06 -The plastic containers must be rinsed, cleaned and emptied completely! -There must not be any hazardous goods labels on the containers! 2. Packaging containing residues of hazardous substances or contaminated by hazardous substances" AVV 15 01 10 * These are completely emptied containers (residues means: < 3 mass % in relation to the container weight) made of metal and plastic from 0.5 to 200 liters from households and commercial sectors with commercially available products (paint, lubricants, personal care products, etc.)

Changes in the context of technical progress and operational advanced development are withheld. The customer is not released from the careful examination of properties. Users shall be responsible for checking the suitability of products for use with materials not mentioned. Thus, our consultation advice is not binding and cannot be used as a basis for liability towards us. We do not accept any liability for damage resulting from improper use. With this, all previous product information becomes invalid. Apart from that, our general terms and conditions in the latest version shall apply.