Lc 2/55

HYDROTEC STICK



DESCRIPTION

The sealing gives the transition area between the top layer and the narrow surface a hydrophobic effect, which prevents moisture from penetrating. Lc 2/55 HydroTec Agent can be used without any problems in all narrow-surface coating processes.

APPLICATION

The HydroTec Stick makes it possible to apply our hydrophobing agent manually. To do this, the stick, which has a sponge at its tip, is drawn vertically over the area of the workpiece to be sealed. The agent is completely absorbed after just one day. The stick can be used for all furniture parts made of wood-based materials as well as for solid wood panels. After application, these are protected against steam, water and dirt in the long term. In addition, the HydroTec Stick prevents the edges from swelling.

AREAS OF USE

EDGE PROCESSING MACHINE

- After buffing wheels

DOUBLE-END PROFILER

- After profiling

PHYSICAL & CHEMICAL DATA

PHYSICAL STATE	liquid
COLOUR	colourless
ODOUR	neutral
INITIAL BOILING POINT	182–208 °C
FLASH POINT	62 °C
DENSITY	0.83 g/cm³
VOC CONTENT	42 % (348.6 g/l)

SAFETY, TRANSPORT & STORAGE

TRANSPORT	Not dangerous goods within the meaning of the transport regulations
HS CODE	34039900
CLASSIFICATION	**Danger** H304 May be fatal if swallowed and enters airways. H413 May cause long lasting harmful effects to aquatic life.
COMPOSITION	Mixture of hydrocarbons (isoalkanes) and 2-methoxy-methylethoxy-propanol
STORAGE	Keep container tightly closed. Store locked up and accessible only to authorised persons. Store in a cool, dry place. Protect from sunlight.
SHELF LIFE	2 years in the unopened container

DISPOSAL

1. Disposal of PE packaging: EWC 15 01 06 – plastic containers must be rinsed, cleaned and completely emptied; no dangerous goods labels may remain on the containers. 2. Packaging containing residues of or contaminated by hazardous substances: EWC 15 01 10* – this refers to completely emptied containers (residues < 3 % by mass of the container weight) made of metal and plastic from 0.5 to 200 litres from households and trade with commercially available products (paint, lubricants, personal care products, etc.).

Subject to change in the course of technical progress and operational development. The customer is not released from carefully checking the properties. Users are responsible for checking the suitability of the products for use on materials not mentioned. Our advice is therefore non-binding and cannot be used as a basis for liability claims against us. We accept no liability for damage resulting from improper use. This product information supersedes all previous product information. In all other respects, our general terms and conditions in their latest version apply.