Lc 5/100

PROTECTING AGENT SPRAYCAN 500 ML



DESCRIPTION

Lc 5/100 Protecting agent Spraycan 500 ml is a silicone-free lubricant and mold release agent. It prevents plastics from adhering to molds, tools and all surfaces.

APPLICATION

Lc 5/100 Protecting agent Spraycan 500 ml is simply sprayed onto the surface to be protected.

AREA OF APPLICATION

- It is used in plastics processing for injection molding, extrusion and multi-component extrusion, pressing, vacuum forming etc.
- It also protects against glue adhesion in wood processing, during edge banding, sprayed onto sliding shoes or pinch rollers.
- Your advantage: significantly clean processing of workpieces. Parts treated with LcM protection agent can then be printed, painted or similarly processed.

PHYSICAL & CHEMICAL DATA

PHYSICAL STATE	Aerosol
COLOUR	Blue
ODOUR	Solvent
INITIAL BOILING POINT	-42 °C
FLASH POINT	-80 °C
DENSITY	not determined
VOC CONTENT	95,50 %

SAFETY, TRANSPORT & STORAGE

TRANSPORT	UN 1950, class 2
HS CODE	38140090
CLASSIFICATION	**Danger** H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H319 Causes serious eye irritation.
COMPOSITION	Mixture of ethanol
STORAGE	Keep the container tightly closed. Store in a cool and dry place. Protect against sunlight
SHELF LIFE	in unopened container for 2 years.

AVAILABLE PACK SIZES

500ml

DISPOSAL

1. Disposal of PE packaging AVV 15 01 06 -The plastic containers must be rinsed, cleaned and emptied completely! -There must not be any hazardous goods labels on the containers! 2. Packaging containing residues of hazardous substances or contaminated by hazardous substances" AVV 15 01 10 * These are completely emptied containers (residues means: < 3 mass % in relation to the container weight) made of metal and plastic from 0.5 to 200 liters from households and commercial sectors with commercially available products (paint, lubricants, personal care products, etc.)

Changes in the context of technical progress and operational advanced development are withheld. The customer is not released from the careful examination of properties. Users shall be responsible for checking the suitability of products for use with materials not mentioned. Thus, our consultation advice is not binding and cannot be used as a basis for liability towards us. We do not accept any liability for damage resulting from improper use. With this, all previous product information becomes invalid. Apart from that, our general terms and conditions in the latest version shall apply.